

## Local Safety Enclosures

Equipped with SOCOMEC Sirco Switches from 125A to 1250A  
Protection Degree IP 55

### SOCOME C Sirco Load break switches

#### Function

SOCOME C SIRCO Manually operated multipolar load break switches. They make and break under load condition and provide safety isolation. Sirco are designed for 415 VAC and DC low voltage electrical circuit. Possibility of adding auxiliary contacts.

Conformity to Standards

> IEC 60947 - 3



SIRCO  
in metal enclosure



SIRCO  
in metal enclosure



## References

### Enclosed Switches

Rating A	No. of pole	Switches	Reference
Material : Metal		Size H400 X W300 X D150mm	
125	3	Sirco	SOSE300125
125	4	Sirco	SOSE400125
160	3	Sirco	SOSE300160
160	4	Sirco	SOSE400160
200	3	Sirco	SOSE300200
200	4	Sirco	SOSE400200
Material : Metal		Size H500 X W400 X D150mm	
250	3	Sirco	SOSE300250
250	4	Sirco	SOSE400250
315	3	Sirco	SOSE300315
315	4	Sirco	SOSE400315
Material : Metal		Size H600 X W500 X D200mm	
315	3	Sirco	SOSE300315
315	4	Sirco	SOSE400315
400	3	Sirco	SOSE300400
400	4	Sirco	SOSE400400
500	3	Sirco	SOSE300500
500	4	Sirco	SOSE400500
630	3	Sirco	SOSE300630
630	4	Sirco	SOSE400630
Material : Metal		Size H800 X W600 X D320mm	
800	3	Sirco	SOSE300800
800	4	Sirco	SOSE400800
1000	3	Sirco	SOSE301000
1000	4	Sirco	SOSE401000
1250	3	Sirco	SOSE301250
1250	4	Sirco	SOSE401250
1600	3	Sirco	SOSE301600
1600	4	Sirco	SOSE401600